



**KLR EA-20|30**

# EA-20|30 — Down-the-Hole Drill

# Excavator-attached DTH drilling

Built on a 20-30-ton excavator, the EA-20|30 delivers reliable DTH drilling with single-pass efficiency and optional dust suppression for quarrying, mining and construction.

## Technical Specifications

### Technical Data

### Parameters

Hole Diameter	5" (127 mm) - 6-3/4" (171 mm)
Single pass Depth Standard Optional	6m 9m
Carrier Make Range	Excavator Sany /Tata Hitachi/Volvo/ Hyundai - SY215/EX215LC/ As Per Customer Request. 20 - 30 Ton
Prime Mover	Excavator Engine
Mast Maximum Pull Up Force Maximum Pull Down Force	5200 Kgf 2700 kgf
Rotatory Head Max Speed Max Torque	0 - 250 rpm 200 Kg.m
Max Speed (Optional) Max Torque (Optional)	0 - 200 rpm 250 Kg.m
Optional	Automatic Rod Changer Dust collector or water injection
Carrier Make Range	Atlas Copco / ELGI 550 Cfm@200psi / As Per Customer Request



+91 90303 27878  
sales@klruniversal.com  
www.klruniversal.com

222/1, Near Nagarjuna Nagar  
Colony, Cherlapally Road, RR  
District, Hyderabad-500062.