



DTHR -150

DTHR -150

Water Well DTHR Series


Hydraulic-powered and built for air, foam, mud rotary and DTH drilling, the DTHR Series adapts to any terrain with ease.

Technical Specifications

Technical Data

Parameters

Hole Diameter DTH (Continuous) DTH (Overburden) Rotary (Continuous) Rotary (Overburden)	4.5" - 6.5" 7" 6"-8" 10"
Depth	100- 150 Meters
Carrier Truck Standard Standard Mounting Optional	4x2 / 4x4 Single Truck Mounting (Compressor + Rig)
Prime Mover	Truck Engine
Formation	Soft / Hard / Unconsolidated / Alluvial
Mast Maximum Pull Up Force Maximum Pull Down Force Maximum Pull Up Speed Rod handling	5200 Kgs 2700kgs 45 Meter/Minute 3m rod handling
Rotatory Head Max Speed Max Torque	0-120 rpm 360 Kg.m
Rod Changer Standard Optiona	Manually Operated Single Rod Changer Automatic Rod Changer (2 truck version)
Air Compressor Make Capacity	Atlas Copco / ELGI / As per customer Request 550 Cfm@ 200 psi / As Per Customer Request
Mud Pump Make Capacity	G&P 5x4
Optional	Only Down The Hole Drill package



+91 90303 27878
sales@klruniversal.com
www.klruniversal.com

222/1, Near Nagarjuna Nagar
Colony, Cherlapally Road, RR
District, Hyderabad-500062.