



TBW 40

KLR
TBW 40

Water Well DTNR Series


Tractor-mounted and hydraulic-powered, the TBW Series is built for air or mud drilling across mixed formations up to 150 metres.

Technical Specifications

Technical Data

Parameters

Hole Diameter	4.5" - 6.5"
Depth	150 Meters
Carrier	New Holland / As Per Customer Request.
Prime Mover	Tractor Engine
Formation	Soft / Hard / Unconsolidated / Alluvial
Mast Maximum Pull Up Force Maximum Pull Down Force Maximum Pull Up Speed Rod Handling capacity	4,500 Kgf 2,400 kgf 35 Meter/Minute 3 meter Rod handling
Rotatory Head Max Speed Max Torque	0-120rpm 270 Kg.m
Rod Changer Standard	Manually Operated Single Rod Changer
Mud pump	Centrifugal pump / Duplex double acting mud pump - Mounted on a separate skid with separate engine
Air Compressor Make Capacity	Atlas Copco / ELGI / As Per Customer Request 600 Cfm@200psi / As Per Customer Request (separate skid mounted)



+91 90303 27878
sales@klruniversal.com
www.klruniversal.com

222/1, Near Nagarjuna Nagar Colony, Cherlapally Road, RR District, Hyderabad-500062.