



**KLR PD1200**

# PD 1200 — Rotary & Auger Drill

# Tractor-mounted rotary/auger rig for fast, clean boreholes


PD 1200 combines a robust mast with high-torque rotary drive and on-board mud handling for efficient foundation, utilities, and civil works across soft, hard, unconsolidated, and alluvial formations.

## Technical Specifications

### Technical Data

### Parameters

Hole diameter (rotary)	300-1200 mm
Hole diameter (auger)	Up to 24" (610 mm)
Max depth	50 m
Carrier	New Holland / As per customer request
Prime mover & power	Tractor engine, 75 HP
Formations	New Holland / As per customer request
Mast	Max pull-up force 4,500 kgf Max pull-down force 2,400 kgf Feed / pull-up speed - 35 m/min
Rotary head (standard) Rotary head (optional)	Max speed 0-200 rpm • Max torque 250 kg·m Max speed 0-160 rpm • Max torque 320 kg·m
Rod handling capacity	Rotary drilling 3 m • Auger drilling 6 m
Rod changer	Tractor engine, 75 HP
Mud pump	On-board 1000 LPM pump (up to 16" drilling); external mud pump for >16"



+91 90303 27878  
sales@klruniversal.com  
www.klruniversal.com

222/1, Near Nagarjuna Nagar  
Colony, Cherlapally Road, RR  
District, Hyderabad-500062.